

## Integrated IP65 T8 Fixtures



### Description

The Uni-light Integrated IP65 fixtures are designed to be used in aggressive applications where maintenance is difficult but good light output is important. The high performance LED's are mounted on a single plate within the enclosure and produce between 95 and 110 lumens per watt. The same highly efficient driver technology that was developed for our ranges of tubes and bulbs is used in this fixture.

The Integrated units are available in 2 foot, or 4 foot lengths with either opaque or clear lens and ratings of 36W or 60W. They are supplied with 18mm grommets for cable entry and stainless steel hangers for mounting.

Output from these integrated units is comparable to our LED tubes at a slightly more competitive price. For instance the 4 foot single width unit rated at 60W will produce 6600 lumens which is comparable to a 4 foot IP65 unit containing 2x36W LED tubes. Ask our distributors for details of pricing and availability.



## Unilight Integrated IP65 T8 Fixtures



### Specification - IP65 T8 Fixture

Model No: UL-KDM-IP65	2F-1T-WW	2F-1T-CW	4F-1T-WW	4F-1T-CW
Nominal Watts W	36	36	60	60
Operating Voltage V	110/240	110/240	110/240	110/240
Frequency Hz	50/60	50/60	50/60	50/60
Light output lm/W	95-110	95-110	95-110	95-110
Dimmable %	100%	100%	100%	100%
Colour Temp K	2700 – 3000	6000	2700 – 3000	6000
Power Efficiency %	90	90	90	90
LED working life hrs	50,000	50,000	50,000	50,000
Height cm	7	7	7	7
Width cm	9	9	9	9
Length cm	120	120	120	120
Warranty Yrs	5	5	5	5
Weight g	1200	1200	1200	1200
Mercury Content	none	none	none	none
EMI	negligible	negligible	negligible	negligible